



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

FIBERFIX Vaxlösning

Article No.

9072

UFI code

EY60-WH7U-6E97-24U6

Synonyms

Paraffin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

For the preparation of paints and as a solvent.

SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites.

SU12 - Manufacture of plastics products, including compounding and conversion.

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

PC32 - Polymer preparations and compounds.

PROC3 - Use in closed batch process (synthesis or formulation).

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises.

PROC5 - Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact).

PROC7 - Industrial spraying.

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities.

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing).

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing).

PROC10 - Roller application or brushing.

PROC11 - Non industrial spraying.

PROC13 - Treatment of articles by dipping and pouring.

PROC14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation.

PROC15 - Use as laboratory reagent.

Identified use(s):

Consumer

Professional

Industry



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

1.3. Details of the supplier of the safety data sheet

Supplier

Färg-In AB

Address

Bodalsvägen 6
681 43 Kristinehamn
Sweden

Telephone

+46 55010045

Email

info@fargin.se

Web site

www.fargin.se

Contact person

Johan Thynell

1.4. Emergency telephone number

See National Telephone Number (112) Poison control center

Available outside office hours

Yes

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Flammable liquids, hazard category 3
Aspiration hazard, hazard category 1
Skin irritation, hazard category 2
Eye irritation, hazard category 2
Acute toxicity, inhalation, hazard category 4
Reproductive toxicity, hazard category 2
Specific Target Organ Toxicity — Repeated exposure, hazard category 1

Hazard statements

H226, H304, H315, H319, H332, H361d, H372

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs .? through prolonged or repeated exposure .?.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container to approved waste receiver.

More information

Contains: styrene , Ethylbenzene , toluene , Xylene.

2.3. Other hazards

This product does not contain any PBT or vPvB substances.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
styrene	100-42-5 202-851-5 01-2119457861-32 601-026-00-0	70 - 90%	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, Acute Tox. 4 - inhalation, Repr. 2, STOT RE 1	H226, H315, H319, H332, H361d, H372 - -	D
xylene	1330-20-7 215-535-7 01-2119488216-32 601-022-00-9	10 - 20%	Flam. Liq. 3, Acute Tox. 4 - dermal, Skin Irrit. 2, Acute Tox. 4 - inhalation	H226, H312, H315, H332 - -	C
Paraffin waxes and Hydrocarbon waxes	8002-74-2 - 01-2119488076-30 -	<6%	-	- - -	-
ethylbenzene	100-41-4 202-849-4 01-2119489370-35 601-023-00-4	1 - 5%	Flam. Liq. 2, Asp. Tox. 1, Acute Tox. 4 - inhalation, STOT RE 2	H225, H304, H332, H373 - -	-
toluene	108-88-3 203-625-9 01-2119471310-51 601-021-00-3	<1%	Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, STOT SE 3 - narcosis, Repr. 2, STOT RE 2	H225, H304, H315, H336, H361d, H373 - -	-

Substance additional information

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen.

Keep the affected person warm and at rest. Get prompt medical attention.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Skin contact

Wash skin with soap and water. Remove contaminated clothing and launder thoroughly before re-use.
Contact physician if irritation persists.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids.
Get medical attention if any discomfort continues.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.
Never give liquid to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.
Harmful if swallowed.
Harmful if inhaled.
Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide or dry powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

In case of fire, toxic gases may be formed.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

Other

Measures in case of fire

Containers close to fire should be removed or cooled with water.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.
Do not smoke or use open fire, or other sources of ignition.
Warn everybody of potential hazards and evacuate if necessary.
If leakage cannot be stopped, evacuate area.
Do not breathe vapour.
Vapours may form explosive air mixtures even at room temperature.
Storage tanks and other containers must be grounded.
Provide adequate ventilation.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.
Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Cover large spillages with foam.
Keep combustibles away from spilled material.
Remove sources of ignition. Beware of the explosion danger.
Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

See section 12.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Avoid spilling, skin and eye contact.
Change contaminated clothing.
Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
Avoid inhalation of aerosols. Flammable/combustible - Keep away from oxidisers, heat and flames.
Keep away from heat, sparks and open flame.
Risk of vapour concentration on the floor and in low-lying areas.
Storage tanks and other containers must be grounded.
Use non sparking handtools and explosion-proof electric equipment.
Even an empty container can contain vapours, with the associated risk of explosion.
Do not use compressed air when cleaning.



SAFETY DATA SHEET

Version number: 38

Issued: 2025-02-10

Replaces SDS: 2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

General hygiene

Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames.

Protect against direct sunlight.

Store in closed original container at temperatures between 5°C and 30°C.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Short-term exposure limit ppm / mg/m ³	Source	Remark	Year
styrene	100-42-5 202-851-5	100 / 430 /	250 / 1080 /	EH40/2005	-	-
xylene	1330-20-7 215-535-7	50 / 220 /	100 / 441 /	EH40/2005	Sk, BMGV	-
ethylbenzene	100-41-4 202-849-4	100 / 441 /	125 / 552 /	EH40/2005	Sk	-
Paraffin waxes and Hydrocarbon waxes	8002-74-2 -	- / 2 /	- / 6 /	EH40/2005	fume	-
toluene	108-88-3 203-625-9	50 / 191 /	100 / 384 /	EH40/2005	Sk	-

DNEL/DMEL

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
styrene (100-42-5/202-851-5)	DNEL	Acute (short term) Inhalation	289 mg/m ³	Workers	Systemic
styrene (100-42-5/202-851-5)	DNEL	Acute (short term) Inhalation	306 mg/m ³	Workers	Local
styrene	DNEL	Chronic (long term)	406 mg/kg bw/day	Workers	Systemic



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
(100-42-5/202-851-5)		Dermal			
styrene (100-42-5/202-851-5)	DNEL	Chronic (long term) Inhalation	85 mg/m³	Workers	Systemic
styrene (100-42-5/202-851-5)	DNEL	Acute (short term) Inhalation	174.25 mg/m³	Consumers	Systemic
styrene (100-42-5/202-851-5)	DNEL	Acute (short term) Inhalation	182.75 mg/m³	Consumers	Local
styrene (100-42-5/202-851-5)	DNEL	Chronic (long term) Dermal	343 mg/kg bw/day	Consumers	Systemic
styrene (100-42-5/202-851-5)	DNEL	Chronic (long term) Inhalation	10.2 mg/m³	Consumers	Systemic
styrene (100-42-5/202-851-5)	DNEL	Chronic (long term) Oral	2.1 mg/kg bw/day	Consumers	Systemic
xylene (1330-20-7/215-535-7)	DNEL	Chronic (long term) Inhalation	77 mg/m³	Workers	Systemic
xylene (1330-20-7/215-535-7)	DNEL	Acute (short term) Inhalation	289 mg/m³	Workers	Local

PNEC/PEC

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
styrene (100-42-5/202-851-5)	PNEC	Freshwater	0.028 mg/l
styrene (100-42-5/202-851-5)	PNEC	Marine water	0.0028 mg/l
styrene (100-42-5/202-851-5)	PNEC	Sediment (freshwater)	0.614 mg/kg
styrene (100-42-5/202-851-5)	PNEC	Sediment (marine water)	0.0614 mg/kg
styrene (100-42-5/202-851-5)	PNEC	Soil	0.2 mg/kg
styrene (100-42-5/202-851-5)	PNEC	Sewage Treatment Plant	5 mg/l

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
xylene (1330-20-7/215-535-7)	PNEC	Freshwater	0.327 mg/l

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

All handling to take place in well-ventilated area.

Personal Protective Equipment Symbols



Eye / face protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Do not use contact lenses.

Hand protection

Chemical resistant gloves required for prolonged or repeated contact.

If signs of wear and tear are noticed then the gloves should be replaced.

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Other skin protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. avoid all skin contact

Respiratory protection

At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used.

Respiratory protection must be used if air contamination exceeds acceptable level.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

White.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Odour

Pungent.

Odour threshold

0,15 ppm

Method

Test reference: Styrene

Melting point / freezing point

-30 - -54 °C

Boiling point or initial boiling point and boiling range

137 °C

Flammability

No data available

Lower and upper explosion limit

1 - 6.6 %

Flash point

24 °C

Method

ISO 1523

Auto-ignition temperature

490 °C

Decomposition temperature

No data available

pH

No data available

Kinematic viscosity

No data available

Solubility

No data available

Water solubility

Insoluble in water.

Partition coefficient n-octanol/water

3

Vapour pressure

6.7 - 12 hPa



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Density and/or relative density

No data available

Relative density

0,89 - 0,92; 23 °C

Relative vapour density

No data available

Evaporation Rate

0,49 - 0,86; (BuAc = 1)

Particle characteristics

No data available

9.2. Other information

Vapour density: 3,6 - 3,66; (luft = 1)

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating may cause a fire or explosion.

10.2. Chemical stability

Stable under normal temperature conditions.

Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

In use may form flammable/explosive vapour-air mixture.

Polymerization can occur.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

Take precautionary measures against static discharges.

10.5. Incompatible materials

Strong acids. Strong oxidising substances. Inorganic peroxides.

Organic peroxides/hydroperoxides.

Strong reducing agents.

10.6. Hazardous decomposition products

Hydrocarbons. Carbon monoxide (CO). Carbon dioxide (CO₂).

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

May be fatal if inhaled. Harmful if inhaled.

Product / Sub-stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Remarks
styrene 100-42-5 / 202-851-5	LD50	5000 mg/kg	Oral	-	Rat	-
styrene 100-42-5 / 202-851-5	LD50	> 2000 mg/kg	Dermal	-	Rat	-
styrene 100-42-5 / 202-851-5	LC50	11,8 mg/l	Inhalation.	4 hours	Rat	-
xylene 1330-20-7 / 215-535-7	LD50	4820 mg/kg	Oral	-	Rat	-
xylene 1330-20-7 / 215-535-7	LD50	4300 mg/kg	Oral	-	Rat	-
xylene 1330-20-7 / 215-535-7	LD50	> 1700 mg/kg	Dermal	-	Rabbit	-
xylene 1330-20-7 / 215-535-7	LD50	> 2000 mg/kg	Dermal	-	Rabbit	-
## missing translation for substance name ## -	ATEmix	4808 mg/kg	Oral	-	-	-
## missing translation for substance name ## -	ATEmix	1996 mg/kg	Dermal	-	-	-
## missing translation for substance name ##	ATEmix	12 mg/l	Inhalation.	-	-	Vapour



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Remarks
-						

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Inconclusive data.

Carcinogenicity

Inconclusive data.

Reproductive toxicity

Contains a substance/a group of substances with possible risk of harm to the unborn child and with possible risk of impaired fertility.

Inconclusive data.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May be fatal if swallowed and enters airways.

Aspiration hazard

Based on available data, the classification criteria are not met.

Toxicity in case of inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

Toxicity in case of skin contact

Irritating.

Toxicity in case of eye contact

Irritating.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Toxicity in case of ingestion

May be harmful if swallowed and enters airways.
Ingestion may cause irritation of the gastrointestinal tract, vomiting and diarrhoea.
Pneumonia may be the result if vomited material containing solvents reaches the lungs.

- 11.2. Information on other hazards
- Endocrine disrupting properties**
- No information available.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity

Harmful to aquatic life with long lasting effects.

Acute fish toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
styrene 100-42-5 / 202-851-5	LC50	3,24 - 4,99 mg/l	96 hours	Pimephales pro- melas (Fat-head Minnow)	flow-through
xylene 1330-20-7 / 215-535-7	LC50	2,66 - 780 mg/l	96 hours	Pimephales pro- melas (Fat-head Minnow)	-

Acute algae toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
styrene 100-42-5 / 202-851-5	EC50	0,46 - 4,3 mg/l	72 hours	Pseudokirchneriella sub- capita
xylene 1330-20-7 / 215-535-7	EC50	11 mg/l	72 hours	Pseudokirchneriella sub- capitata

Acute crustacean toxicity



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
styrene 100-42-5 / 202-851-5	EC50	3,3 - 7,4 mg/l	48 hours	Daphnia magna

12.2. Persistence and degradability

Persistence and degradability

All organic components are considered biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

Product / Substance name CAS / EC no.	LogKow / LogPow	Bioconcentration factor (BCF)	Duration
styrene 100-42-5 / 202-851-5	2,95	74	-
xylene 1330-20-7 / 215-535-7	2,77-3,15	25.9	56 days

12.4. Mobility in soil

Mobility

Product / Substance name CAS / EC no.	KOC
styrene 100-42-5 / 202-851-5	2.55

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

Other adverse effects

No information available.



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Dispose of waste and residues in accordance with local authority requirements.

Waste is classified as hazardous waste.

SECTION 14: Transport information

14.1. UN number

1993

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Styrene, Xylene)

IMDG proper shipping name

FLAMMABLE LIQUID, N.O.S. (Styrene, Xylene)

IATA proper shipping name

Flammable liquid, n.o.s. (Styrene, Xylene)

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

14.3. Transport hazard class(es)

Label
ADR/RID/ADN



3

IMDG



3

IATA



3

ADR / RID Class
3

ADR / RID Classification code
F1

ADR / RID hazard identification number
30

IMDG Class
3

IATA Class
3

ADN Class
3

ADN Class Code
F1



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

14.4. Packing group

ADR / RID / ADN: III

IMDG: III

IATA: III

14.5. Environmental hazards

IMDG Marine Pollutant

No.

14.6. Special precautions for user

Special precautions for user

Tunnel restriction code: D/E

Transport category: 3

IMDG EmS

F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

IBC Instruction: IBC03

Other

Additional information ADR-RID

Limited quantity : 5 L

VE01

274, 601, 604E

Additional information IMDG

Limited quantity : 5 L

Additional information IATA (ICAO)

Limited quantity : 10 L

ERG-kod: 3 L



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National regulations

No data available

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

For further information see attached Exposure Scenario.

SECTION 16: Other information

Changes to previous revision

Formalities

New logo



SAFETY DATA SHEET

Version number:	38
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

FIBERFIX Vaxlösning

Phrase meaning

Flam. Liq. 3 - Flammable liquids, hazard category 3
Asp. Tox. 1 - Aspiration hazard, hazard category 1
Skin Irrit. 2 - Skin irritation, hazard category 2
Eye Irrit. 2 - Eye irritation, hazard category 2
Acute Tox. 4 - inhalation - Acute toxicity, inhalation, hazard category 4
Repr. 2 - Reproductive toxicity, hazard category 2
STOT RE 1 - Specific Target Organ Toxicity — Repeated exposure, hazard category 1
Acute Tox. 4 - dermal - Acute toxicity, dermal, hazard category 4
Flam. Liq. 2 - Flammable liquids, hazard category 2
STOT RE 2 - Specific Target Organ Toxicity — Repeated exposure, hazard category 2
STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure .
H373 May cause damage to organs through prolonged or repeated exposure .

Other

Additional information

This information is based on the information known to us at the time of preparation and it has been given in good faith and on the condition that the product is used under normal conditions and in accordance with the specified method of use. Any other use of the product, if any, together with other products or processes, takes place at the user's own risk.