



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

BHP HÄRDARE

Article No.

9008xx, 9012

UFI code

7M60-VHG7-YE97-ESGX

Synonyms

Liquid Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Hardener.

Identified use(s):

Consumer

Professional

Industry

1.3. Details of the supplier of the safety data sheet

Supplier

Färg-In AB

Address

Bodalsvägen 6

681 43 Kristinehamn

Sweden

Telephone

+46 55010045

Email

info@fargin.se

Web site

www.fargin.se

Contact person

Johan Thynell

1.4. Emergency telephone number

See National Telephone Number (112) Poison control center



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Available outside office hours

Yes

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Organic peroxides, Type D
Acute toxicity, oral, hazard category 4
Skin corrosion, hazard category 1B
Serious eye damage, hazard category 1
Acute toxicity, inhalation, hazard category 4

Hazard statements

H242, H302, H314, H318, H332

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H242 Heating may cause a fire.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H332 Harmful if inhaled.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P370 + P378 In case of fire: Use Foam, carbon dioxide or dry powder. to extinguish.
P501 Dispose of contents/container to approved waste receiver.

More information

Contains: Methyl ethyl ketone peroxides (MEKP) , Butanone



SAFETY DATA SHEET

Version number: 3

Issued: 2025-02-10

Replaces SDS: 2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

2.3. Other hazards

This product does not contain any PBT or vPvB substances.

The mixture does not contain substances $\geq 0.1\%$ of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
Dimethyl phthalate	131-11-3 205-011-6 - -	>55 - <70%	-	- - -	-
Methyl ethyl ketone peroxides (MEKP)	1338-23-4 215-661-2 01-2119514691-43 -	30 - 37%	Org. Perox. A, Acute Tox. 4 - oral, Skin Corr. 1B, Eye Dam. 1, Acute Tox. 4 - inhalation	H240, H302, H314, H318, H332 - -	-
Butanone	78-93-3 201-159-0 - 606-002-00-3	1 - 3%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336 - -	-

Substance additional information

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Get medical attention immediately!

Remove affected person from source of contamination.

Show this safety data sheet to the doctor in attendance.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Inhalation

Move the exposed person to fresh air at once.
If respiratory problems, artificial respiration/oxygen.
Get medical attention.

Skin contact

Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.
Call a doctor if you feel unwell.

Eye contact

Rinse the eye with water immediately.
Immediately transport to hospital or eye specialist. Continue flushing during transport to hospital.
Remove contact lenses, if present and easy to do. Continue rinsing. May cause permanent damage if eye is not immediately irrigated.

Ingestion

Immediately rinse mouth and drink plenty of water. Call an ambulance. Bring along these instructions.
Do not give victim anything to drink if he is unconscious.
Do NOT induce vomiting.
Corrosive lesions can occur in the oral cavity or pharynx.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed or if inhaled.
Causes serious eye damage.
Highly Corrosive.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire can be extinguished using: Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

When heated and in case of fire, toxic vapours/gases may be formed.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Other

Measures in case of fire

Avoid breathing fire vapours.

Containers close to fire should be removed or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

Avoid inhalation of vapours and aerosols and contact with skin and eyes.

Do not smoke or use open fire, or other sources of ignition.

6.2. Environmental precautions

Prevent spillage entering a watercourse or sewer, contaminating soil or vegetation. If this is not possible notify police and appropriate authorities immediately.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

See section 7.

For personal protection, see section 8.

For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

Avoid spilling, skin and eye contact.

Do not smoke or use open fire, or other sources of ignition.

Use explosion proof electric equipment. Use spark-proof tools and explosion-proof equipment.

Container must be kept tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

Protect from heat and direct sunlight.

Store in closed original container at temperatures between 5°C and 25°C.

Store away from reducing substances (eg amines), acids, alkalis and compounds with heavy metals (eg accelerators, drying agents, metallic soap).

Keep flammable liquids away from flammable gas and highly flammable goods.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

7.3. Specific end use(s)

Do not handle until all safety precautions have been read and understood.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Short-term exposure limit ppm / mg/m ³	Source	Remark	Year
Methyl ethyl ketone peroxides (MEKP)	1338-23-4 215-661-2	- / - /	0.2 / 1.5 /	EH40/2005	-	-
Butanone	78-93-3 201-159-0	200 / 600 /	300 / 899 /	EH40/2005	Sk, BMGV	-
Dimethyl phthalate	131-11-3 205-011-6	- / 5 /	- / 10 /	-	-	-

DNEL/DMEL

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	DNEL	Chronic (long term) Dermal	0.54 mg/kg	Consumers	Systemic
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	DNEL	Chronic (long term) Inhalation	0.41 mg/m ³	Consumers	Systemic
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	DNEL	Chronic (long term) Oral	0.27 mg/kg	Consumers	Systemic
Butanone (78-93-3/201-159-0)	DNEL	Chronic (long term) Dermal	412 mg/kg	Consumers	Systemic
Butanone (78-93-3/201-159-0)	DNEL	Chronic (long term) Inhalation	106 mg/m ³	Consumers	Systemic
Butanone (78-93-3/201-159-0)	DNEL	Chronic (long term) Oral	31 mg/kg	Consumers	Systemic
Dimethyl phthalate (131-11-3/205-011-6)	DNEL	Chronic (long term) Inhalation	293.86 mg/m ³	Workers	Systemic
Dimethyl phthalate (131-11-3/205-011-6)	DNEL	Chronic (long term) Inhalation	86.96 mg/m ³	Consumers	Systemic
Dimethyl phthalate	DNEL	Chronic (long term)	25 mg/kg	Consumers	Systemic



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
(131-11-3/205-011-6)		Oral			
Dimethyl phthalate (131-11-3/205-011-6)	DNEL	Chronic (long term) Dermal	60 mg/kg	Consumers	Systemic
Dimethyl phthalate (131-11-3/205-011-6)	DNEL	Chronic (long term) Dermal	100 mg/kg	Workers	Systemic

PNEC/PEC

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	PNEC	Freshwater	0.0056 mg/l
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	PNEC	Marine water	0.00056 mg/l
Methyl ethyl ketone peroxides (MEKP) (1338-23-4/215-661-2)	PNEC	Sewage Treatment Plant	1.2 mg/l
Butanone (78-93-3/201-159-0)	PNEC	Freshwater	55.8 mg/l
Butanone (78-93-3/201-159-0)	PNEC	Marine water	55.8 mg/l
Butanone (78-93-3/201-159-0)	PNEC	Sewage Treatment Plant	709 mg/l
Dimethyl phthalate (131-11-3/205-011-6)	PNEC	Freshwater	0.192 mg/l
Dimethyl phthalate (131-11-3/205-011-6)	PNEC	Marine water	0.0192 mg/l
Dimethyl phthalate (131-11-3/205-011-6)	PNEC	Sediment (freshwater)	1.403 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide explosion proof ventilation for high concentrations.

Provide eyewash station.

Personal Protective Equipment Symbols





SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Eye / face protection

Wear tight-fitting goggles or face shield.

Hand protection

Chemical resistant gloves required for prolonged or repeated contact.

Butyl rubber gloves are recommended. Neoprene. Nitrile.

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Other skin protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Respiratory protection

At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used.

Use respiratory equipment with gas filter, type AX.

Other

Eating, smoking and water fountains prohibited in immediate work area.

Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Promptly remove any clothing that becomes contaminated.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Clear liquid.

Colour

Colourless.

Odour

Slight odour.

Melting point / freezing point

No data available

Boiling point or initial boiling point and boiling range

No data available

Flammability

No data available

Lower and upper explosion limit

No data available



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Flash point

No data available

Auto-ignition temperature

No data available

Decomposition temperature

≥ 60 °C

pH

No data available

Kinematic viscosity

No data available

Viscosity, dynamic

24 mPa · s

Solubility

Miscible with: phthalates.

Water solubility

partially miscible

Partition coefficient n-octanol/water

No data available

Vapour pressure

1 hPa; 84 °C

Density and/or relative density

No data available

Relative density

1.18

Relative vapour density

No data available

Particle characteristics

No data available

9.2. Other information

No data available



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Other

Flash point: Over SADT. No flash point was obtained but the product may release flammable vapors.
Organic peroxides : 30 - 37 %
Active oxygen content: 8,8 - 9,0 %
Decomposition temperature (°C): Test reference: SADT-Self Accelerating Decomposition temperature.
Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is chemically stable under recommended conditions of storage, use and temperature.

10.2. Chemical stability

Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.
Do not use in confined spaces without adequate ventilation and/or respirator.

10.5. Incompatible materials

Conditions/materials to avoid:
Accelerators
Heavy metals
Heavy metal salts
Strong acids.
Strong alkalis.
Strong reducing agents.
Rust
Ash
Pollutions

10.6. Hazardous decomposition products

When heated, toxic and corrosive vapours/gases may be formed. Irritating gases/vapours/fumes of; carbon oxides, formic acid, acetic acid, propionic acid, methyl ethyl ketone (MEK).



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled. Harmful if swallowed.

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Remarks
Dimethyl phthal- ate 131-11-3	-	5000 mg/kg	Oral	-	Rat	Data applies to the component dimethyl phthal- ate, 70% in product.
Dimethyl phthal- ate 131-11-3	LD50	>10 000 mg/kg	dermal	-	rabbit	Data applies to the component dimethyl phthal- ate, 70% in product.
Methyl ethyl ketone peroxides (MEKP) 1338-23-4 / 215- 661-2	LD50	1017 mg/kg	Oral	-	Rat	Data apply to the component methyl ethyl ketone peroxide, 40% in dimethyl phthalate.
Methyl ethyl ketone peroxides (MEKP) 1338-23-4 / 215- 661-2	LD50	4000 mg/kg	Dermal	-	Rabbit	Data apply to the component methyl ethyl ketone peroxide, 40% in dimethyl phthalate.
Methyl ethyl ketone peroxides (MEKP) 1338-23-4 / 215- 661-2	LC50	1,5 mg/l	Inhalation.	4 hours	Rat	Data apply to the component methyl ethyl ketone peroxide, 40% in dimethyl phthalate.

Skin corrosion/irritation

Causes severe skin burns.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Not sensitising.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Toxicity in case of skin contact

Highly Corrosive.

11.2. Information on other hazards

Endocrine disrupting properties

The mixture does not contain substances $\geq 0.1\%$ of substances that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity

The product may have adverse effects on organisms in soil and water.

Acute fish toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
## missing transla- tion for substance name ## -	EC50	5.6 mg/l	72 hours	Pseudokirchneriella subcapitata	OECD 201
## missing transla- tion for substance	LC50	44.2 mg/l	96 hours	Poecilia reticulata (Guppy)	-



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
name ## -					

Acute crustacean toxicity

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
## missing transla- tion for substance name ## -	EC50	39 mg/l	48 hours	Daphnia magna	OECD 202

Micro-/macro organism toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Method / Guideline
## missing translation for substance name ## -	EC10:	12 mg/L	0,5 hours	OECD 209

12.2. Persistence and degradability

Persistence and degradability

The product is easily biodegradable.

Product / Substance name CAS / EC no.	Degradation
Dimethyl phthalate 131-11-3 / 205-011-6	The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.
On basis of test data.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Product / Substance name CAS / EC no.	LogKow / LogPow	Bioconcentration factor (BCF)	Duration of exposure	Species
Methyl ethyl ketone peroxides (MEKP) 1338-23-4 / 215-661-2	< 2,04	10,3	-	-
Butanone 78-93-3 / 201-159-0	0,29	-	-	-
Dimethyl phthalate 131-11-3 / 205-011-6	2,12	5,4	1 days	Fish

12.4. Mobility in soil

Mobility

No data available

12.5. Results of PBT and vPvB assessment

The substance/mixture does not contain any components considered to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) in concentrations of 0.1% or higher

12.6. Endocrine disrupting properties

The mixture contains substances $\geq 0.1\%$ that have endocrine disrupting properties according to Regulation (EC) No. 1907/2006, Article 59(1) or Regulation (EU) 2017/2100 or Regulation (EU) 2018/605.

12.7. Other adverse effects

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Dispose of waste and residues in accordance with local authority requirements.
Waste is classified as hazardous waste.

Packaging

Handle contaminated packages in the same way as the substance itself.

Other

When handling waste, consideration should be made to the safety precautions applying to handling of the product.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

SECTION 14: Transport information

14.1. UN number

3105

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

ORGANIC PEROXIDE TYPE D, LIQUID

IMDG proper shipping name

ORGANIC PEROXIDE TYPE D, LIQUID

IATA proper shipping name

Organic peroxide type D, liquid

14.3. Transport hazard class(es)

Label

ADR/RID/ADN



5.2

IMDG



5.2

IATA



5.2

ADR / RID Class

5.2

ADR / RID Classification code

P1

ADR / RID hazard identification number

539



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

IMDG Class

5.2

IATA Class

5.2

ADN Class

5.2

ADN Class Code

P1

14.4. Packing group

Not applicable

14.5. Environmental hazards

IMDG Marine Pollutant

No.

14.6. Special precautions for user

Special precautions for user

Tunnel restriction code: D

Transport category: 2

IMDG EmS

F-J, S-R

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Other

Additional information ADR-RID

ADR / RID hazard identification number 539

Additional information IATA (ICAO)

Packaging instruction 570.



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
SEVESO-category: P6b, 50t/ 200t

National regulations

No data available

15.2. Chemical safety assessment

Methyl ethyl ketone peroxides (MEKP) : A chemical safety assessment has been carried out.

SECTION 16: Other information

Changes to previous revision

changed substances in 3.2
new UFI



SAFETY DATA SHEET

Version number:	3
Issued:	2025-02-10
Replaces SDS:	2022-12-13

Överensstämmer med förordning (EG) nr 1907/2006 (REACH), bilaga II, ändrad genom kommissionens förordning (EU) nr 2020/878 - Sverige

BHP HÄRDARE

Phrase meaning

Org. Perox. D - Organic peroxides, Type D
Acute Tox. 4 - oral - Acute toxicity, oral, hazard category 4
Skin Corr. 1B - Skin corrosion, hazard category 1B
Eye Dam. 1 - Serious eye damage, hazard category 1
Acute Tox. 4 - inhalation - Acute toxicity, inhalation, hazard category 4
Org. Perox. A - Organic peroxides, Type A
Flam. Liq. 2 - Flammable liquids, hazard category 2
Eye Irrit. 2 - Eye irritation, hazard category 2
STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis
H225 Highly flammable liquid and vapour.
H240 Heating may cause an explosion.
H242 Heating may cause a fire.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

Other

Additional information

This information is based on the information known to us at the time of preparation and it has been given in good faith and on the condition that the product is used under normal conditions and in accordance with the specified method of use. Any other use of the product, if any, together with other products or processes, takes place at the user's own risk.