



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

FIBERFIX Formsläppmedel

UFI code

67QN-9MFP-HA9J-9M40

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product type

Releasing agent.

Relevant identified uses

Professional

Industry

SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites.

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

Not suitable for use in

SU21 - Consumer uses: Private households (= general public = consumers).

Consumer

1.3. Details of the supplier of the safety data sheet

Supplier

Färg-In AB

Address

Bodalsvägen 6

681 43 Kristinehamn

Sweden

Telephone

+46 55010045

Email

info@fargin.se

Web site

www.fargin.se

Contact person

Johan Thynell

1.4. Emergency telephone number

See National Telephone Number (112), Poison control center

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Available outside office hours

Yes

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Flammable liquids, hazard category 2

Eye irritation, hazard category 2

Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Hazard statements

H225, H319, H336

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use Foam, carbon dioxide or dry powder. to extinguish.

P501 Dispose of contents/container to approved waste receiver.

More information

Contains: propan-2-ol , butan-2-ol , methanol



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

2.3. Other hazards

PBT/vPvB: See section 12.
The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.
Vapours are heavier than air and may travel along the floor and in the bottom of containers.
Vapours may cause drowsiness and dizziness.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| Chemical name | CAS No. EC No. REACH No. Index No. | Concentration | Classification | H-phrase M factor acute M factor chronic | Specific concentration limits | Note |
|---|--|---------------|---|--|-------------------------------|---|
| propan-2-ol; isopropyl alcohol; isopropanol | 67-63-0 200-661-7 01-2119457558-25 603-117-00-0 | 40 - 45% | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis | H225, H319, H336 - - | - | - |
| butan-2-ol | 78-92-2 201-158-5 01-2119475146-36 603-127-00-5 | 5 - 10% | Flam. Liq. 3, Eye Irrit. 2, STOT SE 3 - resp. tract irrit., STOT SE 3 - narcosis | H226, H319, H335, H336 - - | - | C |
| methanol | 67-56-1 200-659-6 01-2119392409-28 603-001-00-X | <0.255% | Flam. Liq. 2, Acute Tox. 3 - oral, Acute Tox. 3 - dermal, Acute Tox. 3 - inhalation, STOT SE 1 | H225, H301, H311, H331, H370 - - | - | STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %; |

Substance additional information

For the complete text of H- / EUH-statements mentioned in this section, see section 16.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

SECTION 4: First aid measures

4.1. Description of first aid measures

General first aid, rest, warmth and fresh air.
Do not give victim anything to drink if he is unconscious.
Call a doctor.

Inhalation

Place unconscious person on the side in the recovery position and ensure breathing.
If respiratory problems, artificial respiration/oxygen.
Get medical attention.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water.
If symptoms persist, call a physician.

Eye contact

Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyes wide apart.
Get medical attention immediately. Continue to rinse.

Ingestion

Do NOT induce vomiting.
Rinse mouth.
Get immediate medical advice/attention.

Information for doctors

Treat symptomatically.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Other

Information to rescue personnel

Use personal protective equipment as required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide or dry powder. Aquatic



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

5.2. Special hazards arising from the substance or mixture

Fire causes formation of toxic gases.

Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Wear respiratory protection.

Other

Measures in case of fire

Be aware of danger for fire to re-start.

Move container from fire area if it can be done without risk.

Keep run-off water out of sewers and water sources. Dike for water control.

In case of leakage, eliminate all ignition sources.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

Wash thoroughly after dealing with a spillage.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

Collect and dispose of spillage as indicated in section 13.

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Keep combustibles away from spilled material.

Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

See section 7.

For personal protection, see section 8.

For waste disposal, see section 13.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Avoid inhalation of aerosols and contact with skin and eyes.
Risk of vapour concentration on the floor and in low-lying areas.
When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.
Store above freezing.
Protect from heat and direct sunlight.
Follow rules for flammable liquids.
Flammable/combustible - Keep away from oxidisers, heat and flames.
Keep flammable liquids away from flammable gas and highly flammable goods.
Recommended storage temperature 10 - 30 °C

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure limits

| Ingredient | CAS No. EC No. | Exposure limit ppm / mg/m³ | Short-term exposure limit ppm / mg/m³ | Source | Remark | Year |
|--|----------------------|-------------------------------|---|-----------|--------|------|
| propan-2-ol; isopropyl alcohol; iso- propanol | 67-63-0 200-661-7 | 400 / 999 / | 500 / 1250 / | EH40/2005 | | - |
| butan-2-ol | 78-92-2 201-158-5 | 100 / 308 / | 150 / 462 / | EH40/2005 | | - |
| methanol | 67-56-1 200-659-6 | 200 / 266 / | 250 / 333 / | EH40/2005 | Sk | - |

DNEL/DMEL

| Product/Substance name (CAS No./EC No.) | Type | Exposure | Value | Population | Effects |
|---|------|---------------------|------------------|------------|----------|
| propan-2-ol; isopropyl alcohol; isopropanol | DNEL | Chronic (long term) | 888 mg/kg bw/day | Workers | Systemic |



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

| Product/Substance name (CAS No./EC No.) | Type | Exposure | Value | Population | Effects |
|--|------|-----------------------------------|------------------|------------|----------|
| (67-63-0/200-661-7) | | Dermal | | | |
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0/200-661-7) | DNEL | Chronic (long term) Inhalation | 500 mg/m³ | Workers | Systemic |
| butan-2-ol (78-92-2/201-158-5) | DNEL | Chronic (long term) Dermal | 405 mg/kg bw/day | Workers | Systemic |
| butan-2-ol (78-92-2/201-158-5) | DNEL | Chronic (long term) Inhalation | 212 mg/m³ | Workers | Systemic |
| methanol (67-56-1/200-659-6) | DNEL | Chronic (long term) Inhalation | 260 mg/m³ | Workers | Systemic |
| methanol (67-56-1/200-659-6) | DNEL | Chronic (long term) Dermal | 40 mg/kg bw/day | Workers | Systemic |

PNEC/PEC

| Product/Substance name (CAS No./EC No.) | Type | Environmental compartment | Value |
|--|------|---------------------------|-------------|
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0/200-661-7) | PNEC | Sewage Treatment Plant | 2251 mg/l |
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0/200-661-7) | PNEC | Freshwater | 140.9 mg/l |
| propan-2-ol; isopropyl alcohol; isopropanol (67-63-0/200-661-7) | PNEC | Soil | 28 mg/kg |
| butan-2-ol (78-92-2/201-158-5) | PNEC | Freshwater | 47.1 mg/l |
| butan-2-ol (78-92-2/201-158-5) | PNEC | Soil | 11.58 mg/kg |
| butan-2-ol (78-92-2/201-158-5) | PNEC | Sewage Treatment Plant | 761 mg/l |
| methanol (67-56-1/200-659-6) | PNEC | Freshwater | 20.8 mg/l |
| methanol (67-56-1/200-659-6) | PNEC | Soil | 100 mg/kg |

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

8.2. Exposure controls

Appropriate engineering controls

An eye wash bottle must be available at the work site.

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Provide adequate general and local exhaust ventilation.

Personal Protective Equipment Symbols



Eye / face protection

Wear approved, tight fitting safety glasses where splashing is probable.

Hand protection

Protective gloves should be used if there is a risk of direct contact or splash.

NBR (Nitrile rubber) . Butyl rubber. Viton rubber (fluor rubber).

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Other skin protection

Wear appropriate clothing to prevent any possibility of skin contact.

When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if air contamination exceeds acceptable level.

In case of inadequate ventilation use suitable respirator.

Wear respiratory protection with combination filter (dust and gas filter).

Other

Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Viscous liquid

Colour

Colourless.

Odour

Characteristic.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Melting point / freezing point

No data available

Boiling point or initial boiling point and boiling range

> 82 °C

Flammability

No data available

Lower and upper explosion limit

1.4 - 12.0 vol%; Explosion group: IIB

Flash point

18 °C

Method

CC (Closed cup).

Auto-ignition temperature

> 390 °C

Decomposition temperature

No data available

pH

6.5

Method

DIN 19268

Kinematic viscosity

36 mm²/s

Method

40 °C

Solubility

No data available

Water solubility

easily soluble

Partition coefficient n-octanol/water

No data available

Vapour pressure

< 41 hPa

Density and/or relative density

No data available



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Relative density

0.94

Method

DIN 51757

Relative vapour density

~2,1 (@25 °C)

Explosive properties

In use may form flammable/explosive vapour-air mixture.

VOC %

45% (425g/l)

Particle characteristics

No data available

9.2. Other information

No data available

Other

Conductivity : > 1000 pS/m ; Method : ASTM D 2624

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is chemically stable under recommended conditions of storage, use and temperature.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Strong oxidising substances.

Alkali metals.

Alkali earth metals.

10.6. Hazardous decomposition products

No hazardous decomposition products.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

| Product / Sub- stance name CAS / EC no. | Dose descriptor | Value / Dose | Exposure route | Duration of expos- ure | Test animals |
|--|-----------------|--------------|----------------|---------------------------|--------------|
| propan-2-ol; isopro- pyl alcohol; isopro- panol 67-63-0 / 200-661-7 | LD50 | 5840 mg/kg | Oral | - | Rat |
| propan-2-ol; isopro- pyl alcohol; isopro- panol 67-63-0 / 200-661-7 | LD50 | 16400 mg/kg | Dermal | - | Rabbit |
| propan-2-ol; isopro- pyl alcohol; isopro- panol 67-63-0 / 200-661-7 | LC50 | >25 mg/l | Inhalation | 6 h | Rat |
| butan-2-ol 78-92-2 / 201-158-5 | LD50 | 2193 mg/kg | Oral | - | Rat |
| butan-2-ol 78-92-2 / 201-158-5 | LD50 | >2000 mg/kg | Dermal | - | Rat |
| methanol 67-56-1 / 200-659-6 | LD50 | > 2528 mg/kg | Oral | - | Rat |
| methanol 67-56-1 / 200-659-6 | LD50 | 17100 mg/kg | Dermal | - | Rabbit |
| methanol 67-56-1 / 200-659-6 | LC50 | 128 200 mg/l | Inhalation | 4 hours | Rat |

Skin corrosion/irritation

Irritating.
May be degreasing after frequent contact.

Serious eye damage/irritation

Causes serious eye irritation.
Irritating and may cause redness and pain.

Respiratory or skin sensitisation

Gas or vapour may irritate respiratory system.
May cause drowsiness or dizziness.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

However, ingestion may cause nausea, stomach pain and vomiting.

11.2. Information on other hazards

Endocrine disrupting properties

Contains no substances which cause hormonal disorders (endocrine disorders), according to criteria in (EU) 2017/2100 and (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity

Not classified as dangerous to the environment. However, the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

Acute fish toxicity

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|--|------------------|----------------|----------------------|--|
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | LC50 | 9640 mg/l | 96 hours | Pimephales promelas (Fat-head Minnow) |
| butan-2-ol 78-92-2 / 201-158-5 | LC50 | 2993 mg/l | 96 hours | Pimephales promelas (Fat-head Minnow) |



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Acute algae toxicity

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|--|------------------|----------------|----------------------|--------------------------------|
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | ErC50 | > 1800 mg/l | 96 hours | Scenedesmus quadricauda |
| butan-2-ol 78-92-2 / 201-158-5 | ErC50 | 2029 mg/l | 96 hours | Pseudokirchnerella |
| methanol 67-56-1 / 200-659-6 | ErC50 | 22000 mg/l | 96 hours | Pseudokirchnerella subcapitata |

Acute crustacean toxicity

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|--|------------------|----------------|----------------------|---------------|
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | EC50 | > 10000 mg/l | 48 hours | Daphnia magna |
| butan-2-ol 78-92-2 / 201-158-5 | EC50 | 308 mg/l | 48 hours | Daphnia magna |
| methanol 67-56-1 / 200-659-6 | EC50 | 18260 mg/l | 48 hours | Daphnia magna |

Micro-/macro organism toxicity

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|--|------------------|----------------|----------------------|--------------------|
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | Acute toxicity | > 1050 mg/l | 3 hours | Pseudomonas putida |

Chronical toxicity

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|--|------------------|----------------|----------------------|-------------------------|
| propan-2-ol; isopropyl | NOEC | 1800 mg/l | 7 days | Scenedesmus quadricauda |



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

| Product / Substance name CAS / EC no. | Measurement type | Value / Result | Duration of exposure | Species |
|---|------------------|----------------|----------------------|---------|
| alcohol; isopropanol 67-63-0 / 200-661-7 | | | | cauda |

12.2. Persistence and degradability

53 % Metod: similar to EU Method C.5 & C.6 (propan-2-ol).

Kommentarer: 86 % (similar to EU Method C.5 & C.6) (butan-2-ol).

71,5 - 82,7 % (Respirometric test (BOD of THOD) ECHA) (metanol).

Testperiod: 5 d

The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) : < 10 Method : Leuciscus idus melanotus (metanol)

| Product / Substance name CAS / EC no. | LogKow / LogPow |
|--|-----------------|
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | 0,05 |
| butan-2-ol 78-92-2 / 201-158-5 | 0,65 |
| methanol 67-56-1 / 200-659-6 | -0,77 |
| propan-2-ol; isopropyl alcohol; isopropanol 67-63-0 / 200-661-7 | 0,05 |
| butan-2-ol 78-92-2 / 201-158-5 | 0,65 |
| methanol 67-56-1 / 200-659-6 | -0,77 |

12.4. Mobility in soil

Mobility

The product contains volatile substances, which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

Contains no substances which cause hormonal disorders (endocrine disorders), according to criteria in (EU) 2017/2100 and (EU) 2018/605.



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

12.7. Other adverse effects
No data recorded.

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Disposal considerations
Confirm disposal procedures with environmental engineer and local regulations.
Waste is classified as hazardous waste.

| Waste code | Waste description |
|------------|--|
| 07 02 04* | other organic solvents, washing liquids and mother liquors |

Please note - an asterisk (*) next to a code denotes that it is HAZARDOUS WASTE.

Other
When handling waste, consideration should be made to the safety precautions applying to handling of the product.

SECTION 14: Transport information

14.1. UN number
1987

14.2. UN proper shipping name
ADR / RID / ADN proper shipping name
ALCOHOLS, N.O.S. (vapour pressure at 50 °C not more than 110 kPa) ((Isopropanol; Butanols))

IMDG proper shipping name
ALCOHOLS, N.O.S. ((Isopropanol; Butanols))

IATA proper shipping name
Alcohols, n.o.s. ((Isopropanol; Butanols))

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

14.3. Transport hazard class(es)

Label

ADR/RID/ADN



3

IMDG



3

IATA



3

ADR / RID Class

3

ADR / RID Classification code

F1

ADR / RID hazard identification number

33

IMDG Class

3

IATA Class

3

ADN Class

3

ADN Class Code

F1



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

14.4. Packing group

ADR / RID / ADN: II

IMDG: II

IATA: II

14.5. Environmental hazards

Environmental hazards

No.

14.6. Special precautions for user

Special precautions for user

Tunnel restriction code: D/E

Transport category: 2

IMDG EmS

F-E, S-D

14.7. Maritime transport in bulk according to IMO instruments

No.

Other

Additional information ADR-RID

Limited quantity 1 L

Special Provisions 274 601 640D

Additional information IATA (ICAO)

Packaging instruction 353

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

No data available

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: propan-2-ol, butan-2-ol

SECTION 16: Other information

Changes to previous revision

adjustment to section 2. P313 added. adjusted amount of metanol to 0,25% from earlier 0,20%



SAFETY DATA SHEET

| | |
|-----------------|------------|
| Version number: | 4 |
| Issued: | 2025-05-22 |
| Replaces SDS: | 2022-12-13 |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) No. 2020/878 - Sweden

FIBERFIX Formsläppmedel

Phrase meaning

Flam. Liq. 2 - Flammable liquids, hazard category 2

Eye Irrit. 2 - Eye irritation, hazard category 2

STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Flam. Liq. 3 - Flammable liquids, hazard category 3

STOT SE 3 - resp. tract irrit. - Specific Target Organ Toxicity — Single exposure, hazard category 3 - respiratory tract irritation

Acute Tox. 3 - oral - Acute toxicity, oral, hazard category 3

Acute Tox. 3 - dermal - Acute toxicity, dermal, hazard category 3

Acute Tox. 3 - inhalation - Acute toxicity, inhalation, hazard category 3

STOT SE 1 - Specific Target Organ Toxicity — Single exposure, hazard category 1

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

Other

Additional information

This information is based on the information known to us at the time of preparation and it has been given in good faith and on the condition that the product is used under normal conditions and in accordance with the specified method of use. Any other use of the product, if any, together with other products or processes, takes place at the user's own risk.